

ZX30 SERIES

COMMERCIAL SOLAR LED LIGHTING SYSTEM



PHILIPS
LUMILEDS



LM-79
LM-80

IP66
IK08



The **ZX30** solar lighting system is the most advanced on the market. Ideal for **public parks and pathways**. It integrates a solar module, a battery, and a smart controller all paired with the latest Philips LED lighting technology in a simple and compact design. Installation is therefore easy, quick and secure.

The **ZX30** offers several operating profiles to meet different needs. Light intensity can be dimmed when full power is not required to increase operating hours. Operating profiles can be easily modified thanks to the built-in wireless communication.

FEATURES & BENEFITS

- Weather adaptive technology;
- Automatic activation at sunset and/or before sunrise;
- Dimming options;
- 10 days autonomy without sunlight;
- Wireless communication;
- Flexible operating profiles according to your needs, modifications via remote control.
- No power cables, no trenching;
- > 100 000hrs Philips maintenance free LED operation;
- Universally recognized **common battery group sizes**, easily sourceable locally;
- Easy battery replacement access door;
- Powder coated aluminium housing;
- Quick, easy and safe installation.

APPLICATIONS

- Public parks;
- Walking paths;
- Bicycle paths;
- Boardwalks;
- Bus shelters;
- Community Mailboxes;
- Remote areas.



MANUFACTURED BY:

Solar Vision inc.
www.solar-vision.ca
info@solar-vision.ca
T. : 819-729-0450



LICENSED FOR
CANADIAN WINTERS

ZX30 SERIES

COMMERCIAL SOLAR LED LIGHTING SYSTEM

LIGHTING SPECIFICATIONS		zX30 Solar Lighting System		
Philips Lumileds lumen/Watt	175lm/W			
Luminaire Power (Watt)	6 W	4 W	2.5 W	
Lumens (lm)	1050 lm	700 lm	438 lm	
Dimming / Programmable	Yes, see "Operating Profile" document for details.			
Light Distribution Type	2M, 3M and 5S			
Color temperature (°K)	4000°K, 3000°K, 2200°K or 590nm (Turtle-Friendly Lighting)			
CRI (Color Rendering Index)	70			
LED Lifespan	> 100 000 hours			
Recommended mounting height ft (M)	8 to 14t (2,5 to 4,25 meters)			
Recommended spacing factor	6 x Mounting Height			
Operation	Hours of operation can be divided between evening and morning (before sunrise). The light intensity can also be dimmed. Operating profiles can be modified via remote control, sold separately.			
SOLAR SYSTEM SPECIFICATIONS				
Solar Module Power (Watt)	40 W			
Battery Bank Capacity (Ah)	24Ah @12Vdc (288Wh)			
Battery type	Deep Discharge AGM, GEL			
Battery Overcharge/Discharge protection	YES			
Autonomy (number of days without sunlight)	10 days , with the "weather adaptive technology" and a fully charged battery			
Operating temperature range	-40°C +60°C			
MECHANICAL SPECIFICATIONS				
Solar System mounting	Top of pole, Pole maximum outer diameter: 4" (102mm), Square or Round , (pole not included)			
Luminaire mounting	Horizontal tenon, 2-3/8"Ø dia. (included)			
Unit Weight - lb (Kg) (EPA)	48lb (21.8 Kg) (EPA = 2.7ft ³) including the luminaire			
WARRANTY & CERTIFICATIONS				
Warranty	Solar Module: 25 years Controller: 10 years Batterie: 5 years (prorata) Light fixture : 10 years			
Certifications	Light fixture : CE, UL, cUL, DLC, LM79, LM80 Controller : CE compliant, UL listed to UL1741 and CSA C22.2 No. 107.1-16 UL listed to ANSI/ISA 12.12.01-2015 and CSA C22.2 No. 213-15 Solar Module : TÜV SÜD listed to UL 1703 and IEC 61730			

ZX30 SERIES

COMMERCIAL SOLAR LED LIGHTING SYSTEM

ZX30 ORDERING CODE

Series	OPERATING PROFILE & POWER SELECTION	Morning Mode*	Weather adaptive technology activated**	Color Temperature (°K)	Light Distribution	Sleeve pole shape	Color
ZX30							
	A = Dusk 5h at 6W (1050 lm), OFF	N = NO	N = NO	4000 = 4 000°K	T2 = Type 2M	SQ = Square 4"x4"	BK = Black
	B = Dusk 8h at 4W (700 lm), OFF	Y = YES	Y = YES	3000 = 3 000°K	T3 = Type 3M	RD = Round 4"	SM = Custom
	C = Dusk 12h at 2.5W (468 lm), OFF			2200 = 2 200°K	T5 = Type 5S		
	SM = Custom			590 = 590nm (Turtle-Friendly)			

Example: **ZX30-A-N-Y-4000-T3-SQ-BK** (_ZX30_ - _ _ - _ - _ - _ - _ - _)

*Morning mode, 1 hour from the evening segment will be transferred to the morning segment (1 hour of lighting before sunrise).

** When "weather adaptive technology" is activated, light output is modulated according to environmental conditions.

ACCESSORIES SOLD SEPERATLY

DESCRIPTION	PART NUMBER	NOTES
STRAIGHT POLE ARM (12 Deg.) 2 ft length	#RD212	Otherwise, a standard side of pole tenon is provided for the luminaire installation. See <i>Installation Guide</i> for details. (EPA = ZX + 1.5pi ²)
ARTICULATED ADAPTER ± 20 DEGREES	#TENART20	Allows light redirection.
REMOTE CONTROL	#RC01	Not required for system installation and operation.
BACKLIGHT SHIELD	#BL-SHIELD	Reduce light trespass behind the luminaire.

Contact us to determine which product suits your needs and specific location or for customized solutions. These data are based on the worst month of the year according to the mean daily global insolation provided by Natural Resources Canada for Montreal with solar module facing south.



MANUFACTURED BY:

Solar Vision inc.
www.solar-vision.ca
info@solar-vision.ca
T. : 819-729-0450



LICENSED FOR
CANADIAN WINTERS